


Cross Domain Solutions Data Forwarding Application

Unrivalled Security


What is a Data Forwarding Application?

The Data Forwarding Application (DFA) is one of the Data Pump Application software components. It enables one-way transfer of data streams such as video, audio and sensor data across a BAE Systems Data Diode device. It provides a reliable and high performance mechanism for streaming data securely between two networks of different security domains.



How does it work?

On the source network, the DFA listens for data on a configured TCP or UDP port, and transmits any data received across the Data Diode using a proprietary protocol. On the destination network, the DFA reassembles the data stream in to TCP or UDP packets (depending on the source data stream), and forwards them on to the configured destination IP address.



Key features

- Supports multiple concurrent TCP and UDP data streams, each with their own configurable source port and destination IP address.
- A Quality of Service (QoS) system ensures that bandwidth is shared among all concurrent streams, based on configured priority levels.
- Acts as a protocol break to help prevent malicious packets being transmitted onto the destination network.
- Supports port mapping, so that the same stream can use a different range of ports on the source network from those used on the destination network.
- Provides the capability to send streaming data to a destination endpoint without disclosing its network information to the source host.

Technical Specifications

Supported Protocols	TCP, UDP (Unicast, Multicast, Broadcast)
Bandwidth	Up to 10Gbps (Depending on the type of BAE Systems Data Diode device being used)*
Concurrent Streams	Up to 1024*
Latency	<10ms*
Configuration	<ul style="list-style-type: none">– Console-based Configuration Client– Web Configuration Client (Optional)
Auditing & Monitoring	<ul style="list-style-type: none">– Log files– Syslog– SNMP traps (v1 & v3)– Web Configuration Client (Optional)
Minimum Hardware	<ul style="list-style-type: none">– 8-Core 2.9GHz– 32GB RAM– Fibre NIC (for connection to Data Diode)
Operating Systems	Red Hat Enterprise Linux 6 and 7

* Performance metrics were obtained under ideal lab conditions and vary depending on the size and arrival rate of packets, number of concurrent streams and associated QoS settings, server hardware, and supporting network infrastructure.

For more information contact:
BAE Systems Australia

T: +61 (8) 8480 7799
E: au.ilsales@baesystems.com
W: cds.au.baesystems.com

2486DT00161 Rev A

This document gives only a general description of the product(s) or service(s). It shall not form part of any contract. From time to time, changes may be made in the products or the conditions of supply.

© BAE Systems 2018 all rights reserved. Permission to reproduce any part of this document should be sought from BAE Systems. Permission will usually be given provided that the source is acknowledged and the copyright notice and this notice are reproduced.